



AP-GS802 2-Port GSM Gateway

VoiceFinder AP-GS802 two(2)-Port GSM Gateway provides high-performance Analog or IP to GSM gateway solution including IP-routing services for small enterprise, and other public offices. This product uses the state-of-art technology voice compressed algorithm and unique QoS algorithm of AddPac to maintain the maximum voice quality under fast internet line and slow internet line as well. This product is designed based on high performance RISC CPU + DSP structure; supports upgraded speed, the best quality product, offers various user-friendly functions, manufactured at low cost and this product gives high performance for its price.

AddPac AP-GS802 is a device that can support both GSM gateway service (FXS to GSM or Internet to GSM) and VoIP gateway service (FXS to Internet) simultaneously. It also supports SIP, H.323 Multiple VoIP signaling protocol, various voice codec support(G.711, G.726, G.729, G723.1), two(2) -port GSM interface (antenna, SIM Card), two(2) fast ethernet ports, two(2) FXS interface ports, 1-port RS232C console, Public IP sharing function and state-of-art technologies and services. VoiceFinder AP-GS802 GSM VoIP Gateway supports two(2) 10/100 Base-T fast Ethernet Interface ports and provides stabilized leased line environment, ADSL environment, cable modem environment, fixed IP Address, supports all flow IP environment so that it can be selected in accordance with user environments. It also provides routing function, and internet application function, and offers both VoIP function and IP router function in one platform. So it supports the GSM Gateway solution for SOHO in economical and effective way under fast internet access environment.

Designed on programmable high performance RISC Integrated DSP Technology, AP-GS802 is capable of adopting new capabilities and improvement by downloading firmware from website or with its auto-upgrade option as the customers' needs grow. Moreover, operators can download the latest protocol or service improvements as well as update firmware by checking the version and activating the auto-upgrade via AP-NMS (Network Management System) or AP-VPMS(VoIP Plug &Play Management System) system of AddPac Technologies.

Product Highlights

- Powerful RISC microprocessor and DSP
- Two 10/100 Mbps Fast Ethernet interfaces
- Two(2) GSM Module (Antenna, SIM Card) Interface
- Two(2) FXS Voice Interface (Model B)
- Front panel LEDs that allow you to check the GSM, VoIP and LAN ports in real-time
- VoIP Signaling stacks supporting SIP and H.323 concurrently
- Multi-protocol routing for LAN and WAN access
- Voice Processing
 - VAD, DTMF, CNG, G.168, T.38 G3 Fax Relay
 - Voice Compression Algorithms: G.723, 729A, G.726, and 711
- SNMP MIB V2 for network administration
- Smart, easy Web-based management
- Enterprise VoIP Plug & Play Management System (VPMS) management
- Standard & extended access list for security
- Essential scalability features such as DHCP server & relay, NAT/PAT, IEEE transparent bridging, and debugging/diagnostics
- Remote firmware upgrade using FTP & TFTP
- Cisco-style Command Line Interface (CLI) for expert settings
- Small and compact design
- Power On/Off switches for reliability
- Scalability, authenticity, and reliability ensured due to the installed APOS internetworking software

AP-GS802 Applications

- GSM gateways for SOHO
- FXS to GSM Interworking Service
- IP to GSM Interworking Service
- IP Telephony Service
- VoIP Gateway Service

Hardware Specification

- RISC Microprocessor (CPU) + Voice DSP Processor
- Memory
 - System memory 4Mbyte Flash Memory
 - Main memory 32Mbyte SDRAM
- GSM Interface
 - Two(2) Channel GSM Module
 - Two(2) Antenna Interface
 - Two(2) SIM Card Interface
- PSTN Interface
 - Two(2) FXS Interface(RJ11)
- Ethernet Interface
 - 10/100Mbps 2-port Ethernet (RJ45)
- Console Port
 - RS-232C 1-port Console (RJ45)

Power & Operational environment

- Power Supply VAC 110~220V, 50/60Hz, 15Watt External Power Adaptor
- Temperature 0°C ~ +45°C (operating)
- Temperature -40°C ~ +85°C (storage)
- Humidity 5%~95%

Dimensions

- H x W x D : 38x 182 x 182 (mm)
- Weight : 0.48 (Kg)

IP Routing Protocol

- Static and IEEE802.1Q VLAN Routing

WAN Protocol

- Broadband IP Network
- PPPoE
- Standard Compliant WAN Network Protocol

GSM Service

- GSM two-stage dialing
- GSM Module Management : PIN, IMSI, Power, (No) Shutdown Setting, Up/Down Speed Display, Current Power Level Display
- GSM Inbound call black list & white list
- VoIP Inbound call black list and White List
- LCR (Least Cost Routing)-GSM Traffic Metering
- LCR (Least Cost Routing)-Scheduling
- LCR (Least Cost Routing)-Simulator
- GSM Messaging Service
- GSM SNMP : GSM Standard MIB
- Call Back Service at GSM Port Busy

Voice over IP Service

- H.323, SIP Dual Concurrent VoIP Signaling Protocol
- VAD, DTMF, CNG, G.168, T.38 FAX Relay
- Voice Codec : G.723, G.729, G.726, G.711, etc
- High Level VoIP Signaling Debugging Features
- Polarity Inversion Feature
- Various VoIP Features
- Interoperable with Diverse VoIP Gateways
- Interoperable with Diverse VoIP Gatekeeper, SIP Proxy, MGC

Operation & Management

- Performance Analyzing (Process, CPU, Interface)
- Configuration Backup and Restore for APOS Management
- Debugging and Diagnosis Features
- System Booting/Rebooting through Watch Dog
- Data Logging Features
- IP Traffic Statistics through Accounting
- Debugging/Diagnostic

Network Management

- Standard SNMP Agent (MIB v2) Support
- Console, Telnet, Web Based Management
- Remote Download via FTP/TFTP
- Remote Firmware Upgrade using FTP/TFTP

Traffic QoS Control

- Traffic QoS Control Feature For Services
- Voice, Data Prioritizing Control
- Various QoS Algorithm Support


Security Feature

- IP Packet Filtering / Access List
- Access Control and Data Protections
- Enable/Disable for Specific Protocols
- Multi-level User Account Management
- Auto-disconnect for Telnet/Console Sessions
- PPP User Authentication Support
 - Password Authentication Protocol (PAP)
 - Challenge Handshake Authentication Protocol (CHAP)

Other Features

- DHCP Server and Relay
- Network Address Translation (NAT)
- Port Address Translation (PAT)
- Transparent Bridging (IEEE Standard)
 - Spanning Tree Bridging Protocol
 - Concurrent Routing and Bridging
- NTP (Network Time Protocol)
- Cisco Style Command Line Interface
- Standard Compliant Network Protocol
- AddPac Proprietary IP Sharing
- MAC Address Filtering
- DNS Proxy

Network Configuration



Ordering Information

- AP-GS802: Standard Configuration
- Two (2) Fast Ethernet Port
 - RISC CPU + DSP
 - 2-Port GSM Interface
 - Power ON/OFF Switch
 - External Power Adaptor

VoIP Interface

- Model A: - None
 Model B: - 2-Port FXS Interface

- CAB-LAN Ethernet Cable
- CAB-CON RS-232C Console Cable
- CAB-ANT Antenna Cable