

IPNext320[™] Hybrid IP-PBX System

High-performance Hybrid IP-PBX Solution

IP-PBX Features





AddPac Technology

2012, Sales and Marketing

Contents

- IP-PBX Features
- Smart Multimedia Manager
- VoIP Gateway Features



AP-IP120



IPNext320 Hybrid IP-PBX System





IPNext320 Hybrid IP-PBX System

Signaling Server

- SIP Application Server, Proxy, Registrar and Location Server (RFC3261)
- Multiple ITSP Trunk with SIP & H.323 Accounts Support
 - IP UA Client Role for Registering to ITSP SIP Server
 - H.323 Gatekeeper Client Role for Registering to ITSP H.323 Gatekeeper Server

IVR & Auto Attendant

- Default Auto Attendant Support
- Interactive Voice Response (IVR)
 - Provides with GUI-based Smart IVR Scenario Editor
 - Upload/Download Scenario by Smart IVR Scenario Editor
 - Supports Multiple Concurrent Scenarios
 - Supports Recordable IVR Prompts

Voice Mail

- Support Voice Mail with IVR
- Access from Remote Site via Trunk Support
- Voice Mail Notification Support



IPNext320 Hybrid IP-PBX System

Conference

- G.711 u-law, G.711 a-law, Internal Audio MCU Support
- Ad-hoc Conference
- Dial-Out Conference
- Meet-me Conference
- Multiple External MCU support(Video, Audio, etc): AddPac AP-MC1000, etc
- Conference Chair and Participants Management

Music & Announcement

- Music on Hold
- Replaceable Announcements
- Dialing Music / Tone Service



4

IPNext320 Hybrid IP-PBX System

Number & Call Routing

- Trunk Hunting by Preference or Sequential
- Call Hunting by Preference, Simultaneous, Random
- Call Hunting by Chained Hunting Group
- Partition for Address Grading
- Call Class for Call Access Control
- Number Translation Rule for Inbound/Outbound Call
- Centrex with Prefix Support
- Multiple Shared Devices with One Number
- Multiple Numbers on One Device
- Individual Call Park within Park Number Pool
- Group Call Park within a Group or Other Group
- Call Pickup of Ringing Call of Same Group or Other Group
- Call Pickup of Parked Call
- Call Transfer Blind, Consult
- Call Forwarding Unconditional, Busy, No Answer, Voice Mail
- Call Waiting
- Call Swaping
- Call Hold



IPNext320 Hybrid IP-PBX System

IP-PBX Advanced Features with AddPac IP, Video Phones

- Multiple Call Handling with Call Status and Calling Line Number and Name
- Plug and Play with Auto Discovery Function
- Softkey Map Download and Control
- Time and Date Setting
- Voice Mail List View
- Parked Call List View
- Call Forward Setting
- Recent Call List View
- Calling Number and Name Identification
- Individual Call Park within Park Number Pool by Softkey
- Group Call Park within a Group or Other Group by Softkey
- Call Pickup of Ringing Call of Same Group or Other Group by Softkey
- Call Pickup of Parked Call by Softkey
- Call Transfer Blind, Consult by Softkey
- Call Waiting Indication
- Call Swapping by Softkey
- Call Hold by SoftKey
- Conference Control



IPNext320 Hybrid IP-PBX System

User & Device Management

- LDAP (Light weight Directory Access Protocol) Support
 - Supports Hierarchical Organization
- Auto Discovery of IP Phones & Video Phones
- Monitoring Status of Phones

• Miscellaneous*

- Distinctive Ring by Calling User
- Auto Config & Upgrade
- Intercom
- Personal Directory
- Downloadable Ring
- Do not Disturb






Smart Multimedia Manager

IPNext320 Hybrid IP-PBX System


- Windows based Smart and Easy Management Tool Support
 - Dual Mode Easy Mode and Advanced Mode Support
- User, Device, Call, Conference Management with Intuitive User Interface
- Built in Event Manager or External Event Manager Support
 - Event Configuration with Event Source Filter and Event Logging Filter
 - Event Monitoring with Colorful Format
 - Debug Level Syslog Monitoring Support
 - Event Analysis by Smart Event Analyzer
- Active Call Monitoring Support
- Call Tracing Support
- Active Conference Monitoring Support
- Call History Viewer Support
- Backup, Restore and Initializing of Database Support
- Export and Import of Database to Excel File Support





IPNext320 Hybrid IP-PBX System

- H.323, SIP VoIP Signaling
- H.323
 - ITU-T Standard H.323 v3 Support
 - Support H.245 Tunneling
 - Including H.235 Security Features
- SIP
 - IETF RFC3261 or RFC2543 SIP Standard





H.323

IP Network

(WÁN)

SIP

IPNext320 Hybrid IP-PBX System

• H.323

- Fast connect, normal connect support
- H.245 tunneling support
- Q.931 response message setting for inbound VoIP calls
- H.245 logical channel open timing selection function
- Start H.245 procedure support
- DTMF / Hook flash relay with H.245 alphanumeric / signal
- Secondary gatekeeper support
- Gatekeeper assignment according to the domain name
- Gatekeeper discovery with multicast
- Lightweight RRQ support
- Signaling TCP port assignment
- Resource threshold setting with RAI
- H.235 clear-token, crypto-token support
- canMapAlias support
- Technical prefix (supported prefix) support
- Public IP assignment in NAT environment

SIP

- Gateway-based / Endpoint-based registration support
- Secondary proxy-server assignment function
- SIP signaling port change function
- SIP proxy server assignment according to the domain name
- T.38 real-time fax relay support
- DTMF relay support with RFC2833 / OPTION message
- Re-INVITE support



IPNext320 Hybrid IP-PBX System


Voice Codec

- G.711 A-Law, G.711 U-Law
- G.726 r16, G.726 r32
- G.729A
- G.723.1 r63, G.723.1 r53
- VAD (Voice Activity Detection) function support
- DTMF relay support (H.323, SIP) based on RFC2833

• RTP

- Redundant RTP packet transmission in case of severe packet loss
- Dynamic jitter buffer management and RPT packet jitter and loss compensation with heuristic & DSP error concealment
- Static jitter buffer setting support
- Voice frame per RTP packet number control for each codec
- In-band ring-back tone support
- Virtual ring-back tone support
- Tone parameter change support







IPNext320 Hybrid IP-PBX System

VolP Call Controls

- Hot line connection function with PLAR (Private Line Auto Ring Down)
- Leased line emulation function
- Connection monitoring function
- Fault tolerant with Redundancy and Call Distribution among Gateways for load balancing
- Call attempt with IP address
- H.323, SIP inbound call connection for each voice port
- Multiple E.164 setting for one voice port
- One E.164 or digit pattern can be assigned to more than one voice port
- Hunting with Longest match/ priority/ sequence/ random
- One stage call setup by Digit forwarding
- Call barring with specific digit patterns
- Calling and called number conversion for PSTN outbound calls
- PSTN rerouting in case of VoIP call attempt failure

VolP Call Controls (cont.)

- Call transfer for internal calls
- Call pickup for internal calls
- Calling and called number conversion for VoIP outbound calls
- Calling and called number conversion for VolP inbound calls
- Fax broadcasting call control



IPNext IP-PBX Series

Thank you!

AddPac Technology Co., Ltd. Sales and Marketing

Phone +82.2.568.3848 (KOREA) FAX +82.2.568.3847 (KOREA) E-mail sales@addpac.com

