

## Out-barred-group in Pots(Voip)-peer

Category	S/W Release Version	Date
General	8.10	June. 2004

When a call is initiated via a Voip or Pots peer and its called party number is listed in a pattern-group, the call is restricted.

**APOS Command Script:**  
Restrict the called party number starting with 0001, 0002 and 10

```
!
! Voip peer configuration.
!
dial-peer voice 1000 voip
destination-pattern T
session target ras
dtmf-relay h245-alphanumeric
out-barred-group 0
!
!
!
!
!
!
gatekeeper
!
!
!
! Gateway configuration.
!
gateway
h323-id AddPac-GW
gkip 192.168.0.10 1719 128
register
!
!
!
! Dial Pattern Group configuration.
!
dialpattern-group 0
pattern 0    0001
pattern 1    0002
pattern 2    10T
!
```

## Commands & Syntax

### Configure Out-barred-group

Step	Command	Remark
1	#	Enter APOS Configuration Mode.
	<b># config</b>	
2	(config)# <b>dialpattern-group &lt;tag&gt;</b>	Create Out-barred-group.
3	(config-dialpattern-group#0)# <b>pattern</b> <b>{ &lt;tag&gt;   dial pattern }</b>	Set the numbers to bar.
4	(config-dialpeer-voip-xxx)# <b>out-barred-group &lt;tag&gt;</b>	Apply the group to a voip or pots peer.

### Disable Out-barred-group

Step	Command	Remark
1	(config-dialpeer-voip-xxx)# <b>no out-barred-group</b>	Disable out-barred-group on a voip or pots peer.
2	(config)# <b>no dialpattern-group &lt;tag&gt;</b>	Disable Out-barred-group.

Default : disable